



**HIGH QUALITY CIVIL &
CONSTRUCTION EARTHMOVING
ATTACHMENTS**

HYDRAULIC HAMMERS

- > Available in Small, Medium, Large & Heavy ranges
- > Designed for Extreme Conditions
- > Noise Reduction Technology
- > Fully Shock Absorbed
- > Proven Durability
- > Tried and Tested in





HIGH QUALITY CIVIL & CONSTRUCTION EARTHMOVING ATTACHMENTS



IMPACT BREAKER SPECIFICATIONS

Inward type	Unit	100 Series	200 Series	300 Series	400 Series	430 Series	450 Series	500 Series
Selection of Machine	ton	0.8-2.5	1.2-3.0	2.5-4.5	4.0-7.0	6.0-9.0	7.0-14.0	11.0-16.0
Operation Weight	kg	102	126	152	295	375	571	861
Required Oil Flow Range	l/min	15-25	20-30	25-50	40-70	50-90	60-100	80-110
Operating Pressure	bar	90-120	90-120	90-120	110-140	120-150	130-160	150-170
Impact Range	bpm	800-1400	700-1200	600-1100	500-900	400-800	400-800	350-700
Chisel Diameter	mm	40	45	53	68	75	85	100
Inward Type	Unit	600 Series	700 Series	800 Series	1000 Series	1200 Series	1300 Series	1500 Series
Selection of Machine	ton	15.0-18.0	18.0-21.0	18.0-26.0	25.0-30.0	28.0-30.0	30.0-40.0	40.0-55.0
Operation Weight	kg	1296	1500	1825	2071	2635	2850	3990
Required Oil Flow Range	l/min	90-120	100-150	120-180	150-210	180-240	200-260	210-290
Operating Pressure	bar	150-170	160-180	160-180	160-180	160-180	160-180	160-180
Impact Range	bpm	350-650	350-600	350-500	300-450	300-450	250-400	200-350
Chisel Diameter	mm	125	135	140	150	155	155	175

